

Please amend the present application as follows:

Claims

The following is a copy of Applicants' claims that identifies language being added with underlining ("__") and language being deleted with strikethrough ("—"), as is applicable:

1. (Previously presented) An apparatus, comprising:
 - a frame;
 - a swivel mechanism, said swivel mechanism including a foot having a foot pad of a defined frictional coefficient in contact with a support surface, the foot pad configured with a material that enables rotation of the frame and impedes translational movement of the foot; and
 - secondary feet connected to the frame and disposed in locations surrounding the swivel mechanism, said secondary feet each having a pad of a lower frictional coefficient than the foot pad, wherein said secondary feet pads are configured with a material that enables rotation of the frame when supporting a device on the frame.
2. (Original) The apparatus of claim 1, wherein the swivel mechanism includes a disk connected to the foot.
3. (Original) The apparatus of claim 2, wherein the foot is fixably attached to the disk.
4. (Original) The apparatus of claim 2, wherein the foot is detachable from the disk.

5. (Original) The apparatus of claim 2, wherein the swivel mechanism includes an axle in contact with the disk and secured to the frame with a screw head.

6. (Original) The apparatus of claim 5, wherein the axle is fixably attached to the disk.

7. (Original) The apparatus of claim 5, wherein the axle is configurably coupled to the disk and rotatable with respect to the disk.

8. (Original) The apparatus of claim 2, wherein the swivel mechanism includes a spring at least partially surrounding the axle, the spring supporting the frame.

9. (Original) The apparatus of claim 1, wherein said secondary feet are designed to share a load imposed upon the frame with the foot.

10. (Original) The apparatus of claim 9, wherein the foot supports the majority of the load.

11. (Previously presented) The apparatus of claim 1, wherein the apparatus includes the device disposed on the frame.

12. (Original) The apparatus of claim 11, wherein the device includes a computer display monitor.

13. (Previously presented) The apparatus of claim 1, wherein the material of the secondary feet pads include at least one of an elastomeric material and cork.

14. (Previously presented) The apparatus of claim 1, wherein the material of the foot pad includes at least one of an elastomeric material and cork.